

125NK EURO 5+

ENGINE

Cylinders: Single-cylinder, 4-stroke
Position: Vertical
Engine Model: CFMOTO 158MI
Cooling: Liquid
Bore x Stroke: 58 x 47 mm
Displacement: 124 cc
Compression Ratio: 12:1
Max Power: 10.6 kW (14.4 HP) at 10,500 rpm
Max Torque: 10.2 Nm at 8,500 rpm
Ignition: Electronic
Battery: 12V/7Ah
Spark Plug: NGK PMR9B
Starter: Electric
Fuel System: Electronic Injection
Timing: DOHC, 4 valves
Lubrication: Forced
Fuel: Unleaded gasoline (E5 compatible)
Fuel Consumption: 38 km/l (*)
Fuel Tank Capacity: 12.5 liters
Oil Tank: n.a.
Emission Standard: Euro 5+ (62 g/km CO2)

TRANSMISSION

Clutch: Wet multi-plate
Gearbox: 6-speed
Final Drive: Gear – chain
Top Speed: n.a.

CHASSIS

Frame: High strength steel tubes
Bodywork: -
Front Suspension: Ø 37mm upside-down fork
Front Travel: 119 mm
Rear Suspension: Adjustable monoshock
Rear Travel: n.a.
Brakes: ABS dual-channel system
Front Brake: Ø292 mm disc
Rear Brake: Ø220 mm disc
Front Wheel: 3.00x17MT
Rear Wheel: 3.75x17MT
Front Tire: 110/70R17 M/C
Rear Tire: 140/60R17 M/C
Tire Pressure: Front 2.25 bar / Rear 2.25 bar

DIMENSIONS

L x W x H: 1,990 x 800 x 1,065 mm
Wheelbase: 1,360 mm
Seat Height: 800 mm
Dry Weight: 133 kg
Seat: 2-tier
Approved Seats: 2

EQUIPMENT

Instrument Panel: 5" TFT Digital Display
Storage Compartment: n.a.
Under-seat Storage: -
Lighting: Full LED
License Required: A1