

675SR-R EURO 5+

ENGINE

Cylinders: 3-cylinder, 4-stroke
Position: Front-facing
Engine Model: CFMOTO 372MT-H
Cooling: Liquid
Bore x Stroke: 72 x 55.2 mm
Displacement: 674 cc
Compression Ratio: 11.5:1
Max Power: 66.0 kW (89.8 HP) at 11,000 rpm
Max Torque: 68.0 Nm at 8,250 rpm
Ignition: Electronic
Battery: 12V/11.2 Ah
Spark Plug: TORCH BN8RTI
Starter: Electric
Fuel System: Electronic Injection
Timing: DOHC, 4 valves
Lubrication: Forced
Fuel: Unleaded gasoline (E5 compatible)
Fuel Consumption: 18 km/l (*)
Fuel Tank Capacity: 15 liters
Oil Tank: n.a.
Emission Standard: Euro 5+ (130 g/km CO2)

TRANSMISSION

Clutch: Wet multi-plate
Gearbox: 6-speed
Final Drive: Gear – chain
Top Speed: 219 km/h

CHASSIS

Frame: High strength steel tubes
Bodywork: -
Front Suspension: Ø 41 mm upside-down fork
Front Travel: 136 mm
Rear Suspension: Adjustable monoshock with progressive linkage
Rear Travel: n.a.
Brakes: ABS dual-channel system
Front Brake: Double Ø300 mm disc
Rear Brake: Ø240 mm disc
Front Wheel: MT3.5×17
Rear Wheel: MT5.5×17
Front Tire: 120/70 ZR17 M/C
Rear Tire: 180/55 ZR17 M/C
Tire Pressure: Front 2.30 bar / Rear 2.60 bar

DIMENSIONS

L x W x H: 2,020 x 728 x 1,105 mm
Wheelbase: 1,400 mm
Seat Height: n.a.
Dry Weight: 184 kg
Seat: Double
Approved Seats: 2

EQUIPMENT

Instrument Panel: 5" TFT Digital Display
Lighting: Full LED
Storage Compartment: n.a.
License Required: A