

700MT

ENGINE

Cylinders: Twin-cylinder, 4-stroke
Position: Front-facing
Engine Model: CFMOTO 283MU
Cooling: Liquid
Bore x Stroke: 83 x 64 mm
Displacement: 693 cc
Compression Ratio: 11.6:1
Max Power: 49 kW (66.7 HP) at 9,000 rpm
Max Torque: 60 Nm at 7,250 rpm
Ignition: Electronic
Battery: 12V/12Ah
Spark Plug: NGK CR8EI
Starter: Electric
Fuel System: Electronic Injection
Timing: DOHC, 4 valves
Lubrication: Forced
Fuel: Unleaded gasoline (E5 compatible)
Fuel Consumption: 21 km/l (*)
Fuel Tank Capacity: 18 liters
Oil Tank: n.a.
Emission Standard: Euro 5 (115 g/km CO2)

TRANSMISSION

Clutch: Slipper clutch
Gearbox: 6-speed
Final Drive: Gear – chain
Top Speed: 185 km/h

CHASSIS

Frame: High strength steel tubes
Bodywork: -
Front Suspension: Ø 43 mm USD fork, adjustable preload & damping
Front Travel: 40 mm
Rear Suspension: Adjustable monoshock
Rear Travel: n.a.
Brakes: ABS dual-channel system
Front Brake: Double Ø300 mm disc – 2 pistons
Rear Brake: Ø240 mm disc – 1 piston
Front Wheel: MT3.5x17
Rear Wheel: MT4.5x17
Front Tire: 120/70ZR17M/C
Rear Tire: 160/60ZR17M/C
Tire Pressure: Front 2.25 bar / Rear 2.50 bar

DIMENSIONS

L x W x H: 2,184 x 880 x 1,438 mm
Wheelbase: 1,418 mm
Seat Height: 845 mm
Dry Weight: 207 kg
Seat: 2-tier
Approved Seats: 2

EQUIPMENT

Instrument Panel: 5" TFT Display with Bluetooth
Features: T-Box, USB & USB-C, Ride Modes, Shift Reminder, Speed Alert, Side Cases Mounts, Windshield
Storage Compartment: n.a.
Lighting: Full LED
License Required: A / A2