

700MT ADV

ENGINE

Cylinders: Twin-cylinder, 4-stroke
Position: Front-facing
Engine Model: CFMOTO 283MN-A
Cooling: Liquid
Bore x Stroke: 83 x 64 mm
Displacement: 693 cc
Compression Ratio: 11.6:1
Max Power: 49.0 kW (66.6 HP) at 8,500 rpm
Max Torque: 60.0 Nm at 7,000 rpm
Ignition: Electronic
Battery: 12V/10Ah
Spark Plug: NGK CR9E
Starter: Electric
Fuel System: Electronic Injection
Timing: DOHC, 4 valves
Lubrication: Forced
Fuel: Unleaded gasoline (E5 compatible)
Fuel Consumption: 24.2 km/l (*)
Fuel Tank Capacity: 18 liters
Oil Tank: n.a.
Emission Standard: Euro 5 (98 g/km CO₂)

TRANSMISSION

Clutch: Wet multi-plate, slipper clutch
Gearbox: 6-speed
Final Drive: Gear – chain
Top Speed: 180 km/h

CHASSIS

Frame: Steel trellis frame
Bodywork: -
Front Suspension: KYB Ø 43 mm USD fork, adjustable
Front Travel: 140 mm
Rear Suspension: Adjustable KYB monoshock
Rear Travel: 45 mm
Brakes: ABS dual-channel system
Front Brake: Double Ø300 mm disc with J.Juan radial calipers
Rear Brake: Ø240 mm disc with J.Juan caliper
Front Wheel: Alloy 3.00x19
Rear Wheel: Alloy 4.25x17
Front Tire: 110/80R19
Rear Tire: 150/70R17
Tire Pressure: Front 2.25 bar / Rear 2.50 bar

DIMENSIONS

L x W x H: 2,200 x 845 x 1,330 mm
Wheelbase: 1,540 mm
Seat Height: 820 mm
Dry Weight: 218 kg
Seat: 2-tier
Approved Seats: 2

EQUIPMENT

Instrument Panel: 5" Color TFT Display
Drive Modes: Rain / Sport
Features: Cruise Control, USB port, adjustable windshield, LED lighting, side handle
License Required: A2